



Product Service

CERTIFICATE

No. B 058611 0009 Rev. 00

Holder of Certificate: **Kuoyuh W.L. Enterprise Co. Ltd.**
 No. 17, Kejia 6th Rd.,
 Yunlin County
 64057 Douliu City,
 TAIWAN

Certification Mark:



Product: **Circuit Breaker for Equipment**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 704101834817-00

Valid until: 2023-09-26

Date, 2018-09-27

(Yi Zhu)



Product Service

CERTIFICATE

No. B 058611 0009 Rev. 00

Model(s): 94N series, 94D series

Parameters:

Rated voltage:	AC125/250V
Rated current:	4-16A (details see table 1)
Method of operation:	S-type
Poles No.:	1P
Rated conditional short-circuit current, performance category	
PC1 (I _{nc1}):	500A

<u>94N-</u> (1)	<u>16A-</u> (2)	<u>A</u> (3)	<u>1</u> (4)	<u>B</u> (5)	<u>R</u> (6)
--------------------	--------------------	-----------------	-----------------	-----------------	-----------------

- (1): Means series name; could be 94N or 94D
94N: 94N series
94D: 94D series
- (2): Means rated current; could be 4-16A
More details see table 1
- (3): Means the surface mode of button; could be A or B
A: Circle surface
B: Flat surface
- (4): Means length of terminal; could be 1 or 2
1: 5.5mm
2: 9.5mm
- (5): Means enclosure colour; could be B,W or G
B: Black
W: White
G: Grey
- (6): Means button colour; could be R or B
R: Red
B: Black



Product Service

CERTIFICATE

No. B 058611 0009 Rev. 00

Table 1: Rated current

4A	4.25A	4.5A	4.75A
5A	5.25A	5.5A	5.75A
6A	6.25A	6.5A	6.75A
7A	7.25A	7.5A	7.75A
8A	8.25A	8.5A	8.75A
9A	9.25A	9.5A	9.75A
10A	10.25A	10.5A	10.75A
11A	11.25A	11.5A	11.75A
12A	12.25A	12.5A	12.75A
13A	13.25A	13.5A	13.75A
14A	14.25A	14.5A	14.75A
15A	15.25A	15.5A	15.75A
16A			

Tested according to: EN 60934:2001/A2:2013

Production 085192

Facility(ies):