



WOYR2.E470667 Switches, Appliance and Special Use - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Switches, Appliance and Special Use - Component

[See General Information for Switches, Appliance and Special Use - Component](#)

KUOYUH W L ENTERPRISE CO LTD

E470667

17 KEJIA 6TH RD

DOULIU

YUNLIN HSIEN, 640 TAIWAN

Investigated to ANSI/UL 61058-1

Cat. No.	Load	Amps	Volts	Hz	Temp (°C)	Pol/	Endurance		IP	Dis (mm)	SPCA	Std. Ed.
						Thr/ Cir	30C cycle	55C cycle				
Rocker												
K1-A , K1-B, K1-D or K1-E, f/b A, B, C, D, E, F, G, H, or I, f/b 1, or 2, f/b 1, f/b N, 1, 2, or A, f/b 1, f/b any letter or number, f/b any letter or number, f/b any letter or number, f/b any letter or number, maybe f/b A, or B												
	GP	20	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40	full 1.6	1A, 1B	2013-02-15
	GP	20	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	GP	15	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	GP	15	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	GP	10	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			

	GP	10	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	GP	6	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	GP	6	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	R	20	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	20	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	R	15	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	15	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	R	10	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	10	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	R	6	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	6	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	RM	16(6)	125,250	50-60	T125/55	1/1, 1/2-1.2	6K	10K	40			
	RM	16(6)	125,250	50-60	T125/55	2/1, 2/2-1.3	6K	10K	40			
	RM	12(4)	125,250	50-60	T125/55	1/1, 1/2-1.2	6K	10K	40			
	RM	12(4)	125,250	50-60	T125/55	2/1, 2/2-1.3	6K	10K	40			
	RM	6(4)	125,250	50-60	T125/55	1/1, 1/2-1.2	6K	10K	40			
	RM	6(4)	125,250	50-60	T125/55	2/1, 2/2-1.3	6K	10K	40			
	R	16	28,48	DC	T85/55	1/1, 1/2-1.2	6K	10K	40			
	R	16	28,48	DC	T85/55	2/1, 2/2-1.3	6K	10K	40			
	R	10	28,48	DC	T85/55	1/1, 1/2-1.2	6K	10K	40			
	R	10	28,48	DC	T85/55	2/1, 2/2-1.3	6K	10K	40			
K2-A, K2-B, or K2-C, f/b A, B, C, D, E, F, G, H, I, or J, f/b 1, 2, or 4, f/b 1, 2, 3, 4, or 5, f/b N, 1, 2, or A, f/b 1, f/b any letter or number, f/b any letter or number, f/b any letter or number, f/b any letter or number, maybe f/b A, or B												
	GP	20	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40	full 1.6	1A, 1B	2013-02-15
	GP	20	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			

	GP	15	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	GP	15	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	GP	10	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	GP	10	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	GP	6	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	GP	6	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	R	20	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	20	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	R	15	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	15	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	R	10	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	10	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	R	6	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	6	125,250	50-60	T55	2/1, 2/2-1.3	6K	10K	40			
	RM	16(6)	125,250	50-60	T125/55	1/1, 1/2-1.2	6K	10K	40			
	RM	16(6)	125,250	50-60	T125/55	2/1, 2/2-1.3	6K	10K	40			
	RM	12(4)	125,250	50-60	T125/55	1/1, 1/2-1.2	6K	10K	40			
	RM	12(4)	125,250	50-60	T125/55	2/1, 2/2-1.3	6K	10K	40			
	RM	6(4)	125,250	50-60	T125/55	1/1, 1/2-1.2	6K	10K	40			
	RM	6(4)	125,250	50-60	T125/55	2/1, 2/2-1.3	6K	10K	40			
	R	16	28,48	DC	T85/55	1/1, 1/2-1.2	6K	10K	40			
	R	16	28,48	DC	T85/55	2/1, 2/2-1.3	6K	10K	40			
	R	10	28,48	DC	T85/55	1/1, 1/2-1.2	6K	10K	40			
	R	10	28,48	DC	T85/55	2/1, 2/2-1.3	6K	10K	40			

	R	20	28	DC	T85/55	1/1, 1/2-1.2	6K	10K	40			
	R	20	28	DC	T85/55	2/1, 2/2-1.3	6K	10K	40			
K3-A, K3-B, K3-C or K3-E, f/b A,B,C,D,E,F,G,H or I, f/b 1,2 or 4, f/b 1,2,3,4 or 5, f/b N, 1, 2 or A, f/b 1 or 2, f/b B or W, f/b B, R or N, f/b 0,1,2,3,4,5 or A, f/b N, B, W or R, f/b A												
	GP	16	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	40	full 2.1	-	2013-02-15
	GP	20	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	40			
	GP	25	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	40			
	GP	30	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	40			
	RM	10(8)	125,250	50-60	T125/55	1,2/1,2-1.2,1.3	6K	10K	40			
	RM	16(8)	125,250	50-60	T125/55	1,2/1,2-1.2,1.3	6K	10K	40			
	RM	20(8)	125,250	DC	T125/55	1,2/1,2-1.2,1.3	6K	10K	40			
	R	15	28,48	DC	T85/55	1,2/1,2-1.2,1.3	6K	10K	40			
	R	20	28,48	DC	T85/55	1,2/1,2-1.2,1.3	6K	10K	40			
K3-D, f/b A,B,C,D,E,F,G,H or I, f/b 1,2 or 4, f/b 1,2,3,4 or 5, f/b N, 1, 2 or A, f/b 1 or 2, f/b B or W, f/b B, R or N, f/b 0,1,2,3,4,5 or A, f/b N, B, W or R, f/b A or B												
	GP	16	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	40	full 2.1	-	2013-02-15
	GP	20	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	40			
	GP	25	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	40			
	GP	30	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	40			
	RM	10(8)	125,250	50-60	T125/55	1,2/1,2-1.2,1.3	6K	10K	40			
	RM	16(8)	125,250	50-60	T125/55	1,2/1,2-1.2,1.3	6K	10K	40			
	RM	20(8)	125,250	DC	T125/55	1,2/1,2-1.2,1.3	6K	10K	40			
	R	15	28,48	DC	T85/55	1,2/1,2-1.2,1.3	6K	10K	40			
	R	20	28,48	DC	T85/55	1,2/1,2-1.2,1.3	6K	10K	40			
	GP	16	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	65			

	GP	20	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	65			
	GP	25	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	65			
	GP	30	125,250	50-60	T55	1,2/1,2-1.2,1.3	6K	10K	65			
K5-A, K5-C or K5-D, f/b A,B,C,D,E,F,G,H or I, f/b 1, f/b 1,2 or 3, f/b 1, 2 or A, f/b 1 or 2, f/b B or W, f/b B, R or N, f/b 0,1,2,3,4,5 or A, f/b N, B, W or R, f/b A												
	GP	10	125,250	50-60	T55	1/2-1.2	6K	10K	40	full 1.6	-	2013-02-15
	GP	15	125,250	50-60	T55	1/2-1.2	6K	10K	40			
	GP	20	125,250	50-60	T55	1/2-1.2	6K	10K	40			
	RM	6(4)	125,250	50-60	T125/55	1/2-1.2	6K	10K	40			
	RM	12(4)	125,250	50-60	T125/55	1/2-1.2	6K	10K	40			
	RM	16(6)	125,250	50-60	T125/55	1/2-1.2	6K	10K	40			
	R	10	28,48	DC	T85/55	1/2-1.2	6K	10K	40			
	R	15	28,48	DC	T85/55	1/2-1.2	6K	10K	40			
	R	20	28,48	DC	T85/55	1/2-1.2	6K	10K	40			
K5-B, f/b A,B,C,D,E,F,G,H or I, f/b 1, f/b 1,2 or 3, f/b 1, 2 or A, f/b 1 or 2, f/b B or W, f/b B, R or N, f/b 0,1,2,3,4,5 or A, f/b N, B, W or R, f/b A or B												
	GP	10	125,250	50-60	T55	1/2-1.2	6K	10K	40	full 1.6	-	2013-02-15
	GP	15	125,250	50-60	T55	1/2-1.2	6K	10K	40			
	GP	20	125,250	50-60	T55	1/2-1.2	6K	10K	40			
	RM	6(4)	125,250	50-60	T125/55	1/2-1.2	6K	10K	40			
	RM	12(4)	125,250	50-60	T125/55	1/2-1.2	6K	10K	40			
	RM	16(6)	125,250	50-60	T125/55	1/2-1.2	6K	10K	40			
	R	10	28,48	DC	T85/55	1/2-1.2	6K	10K	40			
	R	15	28,48	DC	T85/55	1/2-1.2	6K	10K	40			
	R	20	28,48	DC	T85/55	1/2-1.2	6K	10K	40			

	GP	10	125,250	50-60	T55	1/2-1.2	6K	10K	65			
	GP	15	125,250	50-60	T55	1/2-1.2	6K	10K	65			
	GP	20	125,250	50-60	T55	1/2-1.2	6K	10K	65			
KY-7 or KY-8, f/b A, B, C, D, E, or F, f/b 1, f/b 1, f/b N, 1, 2, or A, f/b 1, f/b any letter or number, f/b any letter or number, f/b any letter or number, f/b any letter or number, maybe f/b A, or B												
	GP	20	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40	full 2.2	1A, 1B	2013-02-15
	GP	15	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	20	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	R	15	125,250	50-60	T55	1/1, 1/2-1.2	6K	10K	40			
	RM	16(6)	125,250	50-60	T125/55	1/1, 1/2-1.2	6K	10K	40			
	RM	10(4)	125,250	50-60	T125/55	1/1, 1/2-1.2	6K	10K	40			
	R	16	28,48	DC	T85/55	1/1, 1/2-1.2	6K	10K	40			
	R	10	28,48	DC	T85/55	1/1, 1/2-1.2	6K	10K	40			



1A - Switch Button is accessible when the switch is mounting on end-use product.

1B - Additionally evaluated the Glow Wire End Product (GWEP) according to IEC60335-1 Clause 30 (750C, 2 Sec.).

2A - Switch Button is accessible when the switch is mounting on end-use product.

2B - Additionally evaluated the Glow Wire End Product (GWEP) according to IEC60335-1 Clause 30 (750C, 2 Sec.).

2C - IP 65 testing was completed on the exposed switch parts and gasket (seal) to the end product enclosure Category 2. Internal parts were not evaluated for IP ratings and shall be considered in the end product.

Marking: Company name or tradename "KUOYUH" or trademark , catalog, model or part number, electrical ratings and the Recognized Component Mark,  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2015-12-04

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".